Page 3 of 19

1. Amendments to the Claims:

A listing of the entire set of pending claims (including amendments to the claims, if any) is submitted herewith per 37 CFR 1.121. This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Previously Presented) A method of managing fingers for multipath signals in a wireless communication device, said method comprising the steps of:

receiving said multipath signals at said wireless communication device; acquiring one of said multipath signals in a searcher portion of said wireless

communication device:

determining a signal-to-noise ratio (SNR) level of said one of said multipath signals;

evaluating said one of said multipath signals for categorization into one of a plurality of states using at least one SNR threshold;

generating a finger assignment by selectively providing said one of said multipath signals for a demodulation operation based upon its state;

receiving said finger assignment from said searcher portion of said communication device;

determining a signal-strength for said finger assignment;

enabling said finger assignment for a combine operation if said signal-strength for said finger assignment satiates a first signal-strength threshold; and

preventing said finger assignment from being deassigned if said signalstrength of said finger assignment satiates a second threshold, said second signalstrength threshold being less than said first signal-strength threshold.

- 2. (Original) The method recited in Claim 1 wherein said plurality of states includes three hierarchical states.
 - 3. (Original) The method recited in Claim 1 wherein said plurality of states

Page 4 of 19

includes an assigned state, wherein signals associated with said assigned state are used for an active demodulation operation.

- 4. (Original) The method recited in Claim 1 wherein said plurality of states includes a potential state, wherein signals associated with said potential state are not actively used for an active demodulation operation, but which may be likely candidates for a future demodulation operation.
 - 5. (Original) The method recited in Claim 1 wherein said plurality of states includes a temporary state, wherein said temporary state is not actively used for an active demodulation operation, but which may be likely candidates for categorization in a potential state in a future evaluation.
 - 6. (Previously Presented) The method recited in Claim 1 wherein said one of said multipath signals is categorized according to said SNR level of said one of said multipath signals.
- 7. (Previously Presented) The method recited in Claim 1 wherein said one of said multipath signals is categorized according to a time period over which said SNR level of said one of said multipath signals exists.
- 8. (Previously Presented) The method recited in Claim 3 further comprising the step of:

enabling said one of said multipath signals for said demodulation operation if it is categorized in said assigned state.

9. (Previously Presented) The method recited in Claim 1 wherein said first five steps are repeated to provide a quantity of multipath signals at least equivalent to a number of fingers in a receiver portion of said wireless communication device.

Page 5 of 19

10. (Previously Presented) The method recited in Claim 1 further comprising the step of:

determining a time period over which said signal-strength of said finger assignment satiates said second signal-strength threshold.

11. (Previously Presented) The method recited in Claim 10 further comprising the step of:

preventing said finger assignment from being deassigned if said time period satiates a time threshold.

12. (Previously Presented) The method recited in Claim 10 further comprising the step of:

allowing said finger assignment to be deassigned if said finger assignment fails to satiate said time threshold.

13. (Previously Presented) The method recited in Claim 1 further comprising the step of:

allowing said finger assignment to be deassigned if said finger assignment fails to satiate said second signal-strength threshold.

14. (Previously Presented) The method recited in Claim 1 further comprising the step of:

demodulating said finger assignment.

15. (Previously Presented) The method recited in Claim 1 further comprising the step of:

filtering said signal-strength of said finger assignment as determined in said signal-strength determining step.

Page 6 of 19

16. (Previously Presented) The method of Claim 1 further comprising the step of:

categorizing said finger assignment into one of a plurality of states based upon said signal-strength of said finger assignment.

17. (Previously Presented) The method of Claim 10 further comprising the step of:

categorizing said finger assignment into one of a plurality of states based upon said signal-strength of said finger assignment and based upon said time period over which said signals strength exists.

18. (Previously Presented) The method of Claim 16 further comprising the step of:

evaluating said finger assignment for said combine operation or for deassignment based upon its state.

- 19. (Previously Presented) A wireless communication device for managing multipath signals and for managing a finger assignment, said communication device comprising:
 - a searcher adapted to scan for said multipath signals;
 - a transceiver coupled to said searcher;
 - a processor, said processor coupled to said searcher; and
- a computer readable memory unit, said computer readable memory unit coupled to said processor, said computer readable memory unit containing program instructions stored therein that execute, via said processor, and cause the processor to perform the steps of:

receiving said multipath signals at said wireless communication device; acquiring one of said multipath signals in a searcher portion of said wireless communication device;

determining a signal-to-noise ratio (SNR) level of said one of said

Page 7 of 19

multipath signals;

evaluating said one of said multipath signals for categorization into one of a plurality of states using at least one SNR threshold;

generating a finger assignment by selectively providing said one of said multipath signals for a demodulation operation based upon its state;

receiving said finger assignment;

determining a signal-strength for said finger assignment;

enabling said finger assignment for a combine operation if said signalstrength for said finger assignment satiates a first signal-strength threshold; and preventing said finger assignment from being deassigned if said signal-

strength of said finger assignment satiates a second threshold, said second signalstrength threshold being less than said first signal-strength threshold.

- 20. (Previously Presented) The device recited in Claim 19 wherein said plurality of states includes three hierarchical states.
- 21. (Previously Presented) The device recited in Claim 19 wherein said plurality of states includes an assigned state, wherein signals associated with said assigned state are used for an active demodulation operation.
- 22. (Previously Presented) The device recited in Claim 19 wherein said plurality of states includes a potential state, wherein signals associated with said potential state are not actively used for an active demodulation operation, but which may be likely candidates for a future demodulation operation.
- 23. (Previously Presented) The device recited in Claim 19 wherein said plurality of states includes a temporary state, wherein said temporary state is not actively used for an active demodulation operation, but which may be likely candidates for categorization in a potential state in a future evaluation.

Page 8 of 19

- 24. (Previously Presented) The device recited in Claim 19 wherein said one of said multipath signals is categorized according to said SNR level of said one of said multipath signals.
- 25. (Previously Presented) The device recited in Claim 19 wherein said one of said multipath signals is categorized according to a time period over which said SNR level of said one of said multipath signals exists.
- 26. (Previously Presented) The device recited in Claim 21 further comprising the step of:

enabling said one of said multipath signals for said demodulation operation if it is categorized in said assigned state.

- 27. (Previously Presented) The device recited in Claim 19 wherein said first five steps are repeated to provide a quantity of multipath signals equivalent to, or greater than, a number of fingers in a receiver portion of said wireless communication device.
- 28. (Previously Presented) The device recited in Claim 19 further comprising the step of:

determining a time period over which said signal-strength of said finger assignment satiates said second signal-strength threshold.

29. (Previously Presented) The device recited in Claim 28 further comprising the step of:

preventing said finger assignment from being deassigned if said time period satiates a time threshold.

30. (Previously Presented) The device recited in Claim 28 further comprising the step of:

Page 9 of 19

allowing said finger assignment to be deassigned if said finger assignment fails to satiate said time threshold.

31. (Previously Presented) The device recited in Claim 19 further comprising the step of:

allowing said finger assignment to be deassigned if said finger assignment fails to satiate said second signal-strength threshold.

32. (Previously Presented) The device recited in Claim 19 further comprising the step of:

demodulating said finger assignment.

33. (Previously Presented) The device recited in Claim 19 further comprising the step of:

filtering said signal-strength of said finger assignment as determined in said signal-strength determining step.

34. (Previously Presented) The device of Claim 19 further comprising the step of:

categorizing said finger assignment into one of a plurality of states based upon said signal-strength of said finger assignment.

35. (Previously Presented) The device of Claim 28 further comprising the step of:

categorizing said finger assignment into one of a plurality of states based upon said signal-strength of said finger assignment and based upon said time period over which said signals strength exists.

36. (Previously Presented) The method of Claim 34 further comprising the step of:

Page 10 of 19

evaluating said finger assignment for said combine operation or for deassignment based upon its state.

37. (Previously Presented) A computer readable medium containing therein computer readable codes for causing an electronic device to implement a method of managing said multipath signals, said method comprising the steps of:

receiving said multipath signals at said wireless communication device;
acquiring one of said multipath signals in a searcher portion of said wireless
communication device:

determining a signal-to-noise ratio (SNR) level of said one of said multipath signals;

evaluating said one of said multipath signals for categorization into one of a plurality of states using at least one SNR threshold;

generating a finger assignment by selectively providing said one of said multipath signals for a demodulation operation based upon its state;

receiving said finger assignment;

determining a signal-strength for said finger assignment;

enabling said finger assignment for a combine operation if said signal-strength for said finger assignment satiates a first signal-strength threshold; and

preventing said finger assignment from being deassigned if said signalstrength of said finger assignment satiates a second threshold, said second signalstrength threshold being less than said first signal-strength threshold.

- 38. (Previously Presented) The computer readable medium recited in Claim 37 wherein said plurality of states includes three hierarchical states.
- 39. (Previously Presented) The computer readable medium recited in Claim 37 wherein said plurality of states includes an assigned state, wherein signals associated with said assigned state are used for an active demodulation operation.

Page 11 of 19

- 40. (Previously Presented) The computer readable medium recited in Claim 37 wherein said plurality of states includes a potential state, wherein signals associated with said potential state are not actively used for an active demodulation operation, but which may be likely candidates for a future demodulation operation.
- 41. (Previously Presented) The computer readable medium recited in Claim 37 wherein said plurality of states includes a temporary state, wherein said temporary state is not actively used for an active demodulation operation, but which may be likely candidates for categorization in a potential state in a future evaluation.
- 42. (Previously Presented) The computer readable medium recited in Claim 37 wherein said one of said multipath signals is categorized according to said SNR level of said one of said multipath signals.
- 43. (Previously Presented) The computer readable medium recited in Claim 37 wherein said one of said multipath signals is categorized according to a time period over which said SNR level of said one of said multipath signals exists.
- 44. (Previously Presented) The computer readable medium recited in Claim 39 further comprising the step of:

enabling said one of said multipath signals for said demodulation operation if it is categorized in said assigned state.

- 45. (Previously Presented) The computer readable medium recited in Claim 37 wherein said first five steps are repeated to provide a quantity of multipath signals equivalent to, or greater than, a number of fingers in a receiver portion of said wireless communication device.
- 46. (Previously Presented) The computer readable medium recited in Claim 37 further comprising the step of:

Page 12 of 19

determining a time period over which said signal-strength of said finger assignment satiates said second signal-strength threshold.

47. (Previously Presented) The computer readable medium recited in Claim 46 further comprising the step of:

preventing said finger assignment from being deassigned if said time period satiates a time threshold.

48. (Previously Presented) The computer readable medium recited in Claim 46 further comprising the step of:

allowing said finger assignment to be deassigned if said finger assignment fails to satiate said time threshold.

49. (Previously Presented) The computer readable medium recited in Claim 37 further comprising the step of:

allowing said finger assignment to be deassigned if said finger assignment fails to satiate said second signal-strength threshold.

50. (Previously Presented) The computer readable medium recited in Claim 37 further comprising the step of:

demodulating said finger assignment.

51. (Previously Presented) The computer readable medium recited in Claim 37 further comprising the step of:

filtering said signal-strength of said finger assignment as determined in said signal-strength determining step.

52. (Previously Presented) The computer readable medium recited in Claim 37 further comprising the step of:

categorizing said finger assignment into one of a plurality of states based

Page 13 of 19

upon said signal-strength of said finger assignment.

53. (Previously Presented) The computer readable medium recited in Claim 46 further comprising the step of:

categorizing said finger assignment into one of a plurality of states based upon said signal-strength of said finger assignment and based upon said time period over which said signals strength exists.

54. (Previously Presented) The computer readable medium recited in Claim 52 further comprising the step of:

evaluating said finger assignment for said combine operation or for deassignment based upon its state.